

5476 and 5488V Twinax Terminals



Compatibility

The **CLI/5476** is completely compatible with IBM InfoWindow 3476, with additional emulation for 3197C and 3197D.

The **CLI/5488V** is compatible with the IBM 3488 which supports Shared-Addressing, the ability to use 4 display sessions while using only 1 host address on the AS/400. CLI/5488V can also emulate as an IBM 3197C, 3197D, 3486, or 3487.

Affordability

CLI Modular Display Station is designed for easy connection to the IBM AS/400 and S/3X. With its features and reliability, it is the most cost effective solution in the market. Keeping in mind that this unique modular design also provides real protection of your investment for future migration to PC and NC.

Investment Protection

Base logic unit, monitor, keyboard of CLI modular display station are separate units, which can be mixed and matched to your requirements. The PC compatible monitor and keyboard can be used by any PC or NC. The base logic unit can be configured as a stand alone protocol converter to drive your desktop or system printers.

5476 and 5488V Twinax Terminals Specifications

Specifications and Features	5476	5488V
Total Sessions	7	4/7
Maximum Display / Printer Sessions	7/1	7/1
Shared Addressing		.
3476 Emulation	.	
IBM 3197C (Color) / 3197D (132 Column Mono) Emulation	.	.
IBM 3486 / 3487 / 3488 InfoWindow II Emulation		.
AS/400 OS/400 / System/38 CPF / System/36 SSP	.	.
IBM 5294, 5394, 5494 Remote Controllers Compatible	.	.
4214, 5224, 5256, 5219, 3812 Printer Emulation	.	.
Host Addressable / Local Printer Port	.	.
HP Laserjet, IBM, Epson, Okidata, Panasonic, Barcode and Compatible Printers	.	.

Custom Printer Support	.	.
ASCII Passthru and HEX Transparent Mode Support	.	.
Computer Output Reduction (COR) Support for Laser Printers	.	.
Screen Print with Trim	.	.
Split Screen (In Monochrome): 25 & 17	.	.
Split Screen (In Color): 25 & 25	.	.
122-key Typewriter 5250 Style Terminal Keyboard Support	.	.
101-Key, 102 Key, 84-Key Keyboard Support	.	.
Play/Record and Pause/Quit Functions with 1520 Keystrokes Buffer with Erase Function	.	.
Use Any Size Color or Monochrome PC VGA or SVGA Monitor as Display Screen	.	.
Reverse Image with Overscan Display (Monochrome Monitor)	.	.
256K Colors Customizable Color Palette	.	.
Selectable Column Separator Style (Bar or Dot Style)	.	.
Selectable Character Set for Display (Serif or Sans Serif)	.	.
Adjustable Auto Dim Timer with Power Saver	.	.
Flash Alarm for Industrial or Loud Environment	.	.
80 Columns X 24 Rows (1920-Character Standard Display)	•	•
132 Columns X 27 Rows (3564-Character Standard Display)	•	•
Vital Product Data Support	•	•
Allows Dedicated Bar Code Reader Input (No Keyboard Required)	•	•
Barcode Decoder and Scanner Compatibility	•	•
Extended Character Buffer		•
Mouse Support, Hotspots		•
Built-in Calculator		•
Temperature: 50°F-105°F (10°C-40°C)	•	•
Relative Humidity 8 - 80%	•	•
Power: 100-127 VAC, Single Phase 3-Wire 60 Hz, 0.2 AMPS @120 VAC Power: 210-230 VAC, Single Phase 3-Wire 50 Hz, 0.4 AMPS @220 VAC	•	•
Dimensions: 12 1/2"W x 12 1/4"D x 2 1/4" H	•	•