

MT1200c Thin Client

Model:

MT1200c - Powerful, basic terminal includes stable, industry-standard Microsoft Windows CE operating system; Microsoft RDP and Citrix ICA protocol to access Windows applications

All models include:

- Small footprint, including monitor mounting system, to conserve space and ease installation and use
- Multiple simultaneous session support to increase productivity
- 10/100 BaseT Fast Ethernet, USB, and audio ports to simplify network and peripheral connection and unit deployment, reducing installation time to just minutes
- No fan or other moving parts for quiet operation and high reliability
- Locked down, sealed box design for high security and virus prevention
- Seamless, centralized management with bundled CLI SNMP Administrator software, including remote shadowing and asset tracking to give administrators complete control of all CLI desktops, dramatically reducing support costs
- Lower total cost of ownership (TCO) than PCs or other computing products



Hardware Specifications

Model	MT1200c
CPU	<ul style="list-style-type: none"> • AMD Geode GX
Flash memory	<ul style="list-style-type: none"> • 32MB, expandable to 512MB
DRAM	<ul style="list-style-type: none"> • 64MB, expandable to 512MB
Network	<ul style="list-style-type: none"> • Auto-sense 10/100BaseT twisted-pair Ethernet, RJ-45 connector, Wake-On-LAN
I/O ports	<ul style="list-style-type: none"> • Four Type A USB 2.0
Video	<ul style="list-style-type: none"> • Resolution up to 1600 x 1200 • Up to 24-bit (16M) colors • Up to 100 Hz refresh rate, flicker free
Audio	<ul style="list-style-type: none"> • Full 16 bit stereo FM synthesis, stereo line-out, 8-bit mini microphone line-in
Physical specifications	<ul style="list-style-type: none"> • Dimensions: 5.4 in (W) x 7.8 in (D) x 2.0 in (H) • Weight: 1.4 lb • VESA 100-compliant mounting holes (monitor mounting kit included)
Environment	<ul style="list-style-type: none"> • Operating temperature: 5°C to 30°C (41°F to 86°F), Storage temperature: -40°C to 60°C (-41°F to 140°F) • Relative humidity: 20% to 80% non-condensing • Power requirements: 100-240 VAC, 50/60 Hz • Convection cooling, no fan
Regulatory compliance	<ul style="list-style-type: none"> <li style="width: 50%;">• FCC Class B <li style="width: 50%;">• CE Mark <li style="width: 50%;">• UL <li style="width: 50%;">• TÜV

Software Specifications

Model	MT1200c
Local Operating System	<ul style="list-style-type: none"> • Microsoft Windows CE 5
RDP	<ul style="list-style-type: none"> • Microsoft RDP 5.5, including port redirect and session auto reconnection
ICA	<ul style="list-style-type: none"> • Citrix ICA 8, including full Program Neighborhood Agent
Other features	<ul style="list-style-type: none"> • VNC • Elo and Microtouch touch screen support • ThinPrint • Supports optional Castles Technology EZ100 external smart card reader via serial or USB
Enhanced printing capability	<ul style="list-style-type: none"> • Local print screen
Security	<ul style="list-style-type: none"> • Multiple levels of security including user lock-out
Remote configuration / management	<ul style="list-style-type: none"> • DHCP, SNMP, FTP • CLI SNMP Administrator software, including configuration and image updates, shadowing, asset management, registry edit, Eboot for flash disaster recovery
Server Operating System compatibility / support	<ul style="list-style-type: none"> • Microsoft Windows Server 2003, Windows 2000 Server, and Windows NT 4.0, Terminal Server Edition • Citrix® MetaFrame® Presentation Server for Windows®, MetaFrame® XP™, MetaFrame® for UNIX and WinFrame®
Languages	<ul style="list-style-type: none"> • English (US and UK), Italian, French, Canadian French, Chinese, Austrian / German, Scandinavian, Spanish, Japanese / Kana, Korean

