

Models: withdrawn see MT1500

ET1500e - Windows CE.NET, RDP, ICA

ET1500n - Windows CE.NET, RDP, ICA, IE

## ET1500 Features and Benefits:

- **Stable, industry-standard Microsoft Windows CE .NET operating system**
- **Microsoft RDP and Citrix ICA protocol to access Windows applications**
- **VT-100 terminal emulation to access UNIX applications**
- **Internet Explorer browser (ET1500n) to access Web-based applications**
- **Small footprint and internal power supply to reduce clutter and ease installation and use**
- **Multiple simultaneous session support to increase productivity**
- **No fan or other moving parts for quiet operation and high reliability**
- **Highly secure and virus proof**
- **Centralized management with bundled CLI SNMP Administrator software, including remote shadowing and asset tracking**

**800/218/5207**

**[www.datasystemsplus.com](http://www.datasystemsplus.com)**

# ET1500

## Windows CE. NET Thin Client



The ET1500 thin client, with its high quality, exceptional value, and superior ease of use, is a terminal that gives users the ability to access Windows, UNIX, and Internet applications, at a lower total cost of ownership than PCs or other computing products.

The ET1500 client software, based on industry standard Microsoft Windows CE .NET, has built-in support of Microsoft RDP and Citrix ICA protocols, VT terminal emulation and Internet Explorer (ET1500n). Users can access Windows applications running on central servers including Microsoft Windows Server 2003 and Citrix MetaFrame XP, as well as UNIX and Web-based applications. This standard software provides broad application compatibility and system integration, improving user productivity.

Serial and parallel printer ports, 10/100 BaseT Fast Ethernet, USB and PS/2 ports, audio and an internal power supply are all standard ET1500 hardware contained in a small footprint package. This simplifies network and peripheral connection and unit deployment. Typical installation time for the ET1500 is less than five minutes.

The ET1500 is a highly secure, "locked down" sealed box. No applications or data are stored locally; instead both reside on the central server. This protects valuable applications and data from accidental corruption or loss, theft, or infection by viruses, minimizing downtime.

And like all CLI thin clients, the ET1500 works seamlessly with CLI's SNMP Administrator software. This powerful tool gives administrators complete centralized control of all CLI desktops, dramatically reducing support costs.

**Computer Lab**  
International. 

# **ET1500 Technical Specifications 800/218/5207**

## **Local Operating System**

- Microsoft Windows CE .NET

## **Software Features**

- Microsoft RDP 5
- Citrix ICA v.6 protocol
- Terminal Emulation
  - VT-100
- Windows CE .NET Internet Explorer Web Browser 5.5 (ET1500n)
  - Frames
  - Tables
  - Cascading style sheets
  - Javascript interpreter (JScript)
  - DHTML
  - JPEG and animated GIF images
  - WAV files
- LPD Server
  - Universal printer support via local LPD server
- Microtouch touch screen support

## **Exclusive CLI Enhancements to Windows CE .NET**

- Security
  - Multiple levels of security including user lock-out
- "Your U.I."
  - Select from standard CE Terminal Manager user interface, complete lock-down Connect-Button interface or easy to use CLI / TaskBar interface which makes task switching easy and intuitive
- Configuration Updates
  - Push of configuration updates using less than 240k bandwidth
- Registry Modification
  - Full control including registry edit for maximum flexibility
- Asset Management
  - Unique serial number embedded in all devices to allow asset tracking
- Image Copy
  - Create a standard configuration on one device and copy it to one or thousands without user intervention
- CE Shadow
  - Remotely "view" any device for faster configuration and help desk support

## **Remote Configuration Services**

- DHCP
- SNMP
- FTP
- SNMP Administrator software for remote management

## **Server Operating System Compatibility / Support**

- Microsoft Windows NT 4.0, Terminal Server Edition
- Microsoft Windows 2000
- Microsoft Windows Server 2003
- Citrix MetaFrame, MetaFrame XP and MetaFrame for UNIX
- Citrix WinFrame
- UNIX

## **Base Hardware**

- 233 MHz CPU
- 16MB Flash memory
- 32MB DRAM (ET1500e) 64MB DRAM (ET1500n)

## **Network**

- Auto-sense 10/100BaseT twisted-pair Ethernet
- RJ-45 connector

## **I/O Ports**

- One serial DB-9 RS-232C up to 115.2K baud
- One parallel DB-25 Centronics / PC compatible
- One PS/2 mini-DIN keyboard
- One PS/2 mini-DIN mouse
- One Type A USB

## **Languages**

- English (US and UK)
- Italian
- French
- Canadian French
- Chinese
- Austrian / German
- Scandinavian
- Spanish
- Japanese / Kana
- Korean

## **Video**

- Resolution up to 1024x768 SVGA
- 256 Colors / high-color / true color
- Up to 85Hz refresh rate, flicker free

## **Audio**

- Full 16 bit stereo FM synthesis
- Stereo line-out
- 8 Bit mini microphone line-in

## **Physical Specifications**

- Width x Depth x Height: 2 in x 11.25 in x 9.5 in
- Weight: 3.3 lb

## **Environment**


- Operating temperature: 5°C to 40°C (41°F to 104°F)
- Storage temperature: -40°C to 60°C (-41°F to 140°F)
- Relative humidity: 20% to 80% non-condensing
- Power requirements: 100-240 VAC, 50/60 Hz
- Convection cooling, no fan

## **Regulatory Compliance**

- FCC Class A
- UL
- CE
- TÜV

## **Warranty**

- Three-year return-to-depot



CLI continually improves products as new technologies become available, and therefore reserves the right to change specifications without prior notice. Copyright 2003 CLI, Inc. All rights reserved. Computer Lab International™ is a trademark of CLI, Inc. All other trademarks used are the properties of their respective owners.  
062403